



Made in
Australia

BERENDS

Folding TH100

Hydraulically folding tandem disc plough

- Excellent digging ability
- Available in 28, 32, 36, 40, 44 and 48 plate models at 9" disc spacings.
- Fitted with 24" x 5mm, 24" x 6mm, 26" x 6mm or 28" x 8mm scalloped discs. All discs are European Bellota Boron discs which carry a *lifetime warranty* against manufacturing failure.



- All models are fitted with hydraulic gang adjustment which allows the gangs to be folded parallel with the main frame to be under 2.4m overall width.
- Gangs can also be opened right up to no angle at all when only a fine till of the topsoil is required.
- Solid cast spools throughout the gangs provide ballast weight in the gangs, where it counts, rather than the main frame. Each is individually machined to suit the disc for extra strength.



Picture above: 40 plate model shown fully closed up for transport



Made in Australia

- Flanged disc bearings designed specifically for severe tillage applications. The bearings are encapsulated in two case hardened zinc plated stampings. Two nitrile 'O' rings are fitted to exclude contaminants and provide a grease seal to ensure lubricant goes directly into the bearing.



- Buster tine removes centre ridge to create a level finish.
- Integrated furrow fillers are standard.
- Fitted with four Land Cruiser wheels on a 5 ton axle. Hydraulic wheel lift is standard.
- 40mm square high tensile gang bolts.

- Fully adjustable drawbar height with parallel lift for better transportation.
- Wheelkit locking arms reduce stress on the hydraulics when transporting.
- Australian made Ryco hoses are used with a minimum burst pressure of 20,400 psi.
- Australian made Eaton cylinders.
- Prong type scrapers are standard - formed scrapers on request.
- Parking jack is standard.



	28 plate	32 plate	36 plate	40 plate	44 plate	48 plate
Approx Weight	3290kg	3500kg	3680kg	3830kg	3980kg	4130kg
No. bearings	12	16	16	16	20	24
No. axles	4	8	8	8	8	12
Cutting Width	3.43m (11'3")	3.88m (12'9")	4.33m (14'3")	4.80m (15'9")	5.26m (17'3")	5.71m (18'9")

Note: Cutting width does not include the width of the two furrow filler discs



John Berends Implements Pty Ltd

130 Frankston-Dandenong Rd, Dandenong South, Vic. 3175

Ph: (03) 9791 2494 Fax: (03) 9794 5568

email: berends@johnberendsimplements.com.au

www.johnberendsimplements.com.au