

BERENDS

Twin Rotor Slashers

Heavy duty slashers designed for tough conditions - available in trailing or linkage models

5 YEAR
GEARBOX
WARRANTY



**Made in
Australia**

- Available in 8', 10' and 12' in three point linkage models, or 10' and 12' in the trailing models.
- Bondioli & Pavesi Series 7 main pto driveshaft.
- Rotors are not timed (3mm gap) and are fitted with two-plate adjustable slip clutches between each gearbox for protection.
- 110 HP oil lubricated Italian gearbox in the centre drives the two 75 HP outer gearboxes.
- Trailing models fitted with 14" Ford tyres and linkage models are fitted with 8" solid rubber wheels as standard. Puncture proofing is available on the trailing model. Adjustment is via ratchet or optional hydraulic ram (Code 0118)
- Contra rotating heavy duty rotors form two small outer windrows however a flat windrow behind the centre of the slasher can be created by reversing the rotor direction. Fitted with stepped blades.
- The 6mm top deck is reinforced by 100 x 50 x 6mm RHS and 10mm gearbox mount plates provides incredible strength.
- Front and rear chains fitted as standard.
- Optional wide angle joints available on request.

SPECIFICATIONS

Model	2.4m (8') Linkage (0101)	3.0m (10') Trailing (0102)	3.0m (10') Linkage (0104)	3.6m (12') Trailing (0112)	3.6m (12') Linkage (0114)
Cutting Width	2.3m	2.9m	2.9m	3.5m	3.5m
Overall Width	2.52m	3.12m	3.12m	3.72m	3.72m
Weight	720kg	925kg	975kg	1025kg	1075kg
Tractor HP	50HP +	60HP+	70HP+	70HP+	80HP+



John Berends Implements Pty Ltd

130 Frankston-Dandenong Rd, Dandenong South, Vic. 3175

Ph: (03) 9791 2494 Fax: (03) 9794 5568

email: sales@johnberendsimplements.com.au www.johnberendsimplements.com.au