

## Pasture Toppers

Made in Australia



The high speed pasture topper gives superior sharp, clean cutting promoting pasture rejuvenation.

- 3mm top deck with rhs structural support providing extra strength SPECIFICATIONS
- Fitted standard with adjustable skids providing a cutting height of over 200mm
- Twin springsteel rotors fitted with twisted and deeply stepped Boron blades create an uplift effect whilst topping resulting in a cleaner cut and more even spread of the cut material out the back.
- Fitted as standard with 45 HP outer gearboxes and 75HP centre gearbox. Optional 75HP outer gearboxes are also available.
- All gearboxes are Italian made and oil lubricated and come with a **5 Year Manufacturers Warranty**.

| Model                         | 10' (3.0m)              |
|-------------------------------|-------------------------|
| Code                          | 0115 (45HP) 0116 (75HP) |
| <b>Cutting Width</b>          | 2900mm                  |
| Overall Width                 | 3120mm                  |
| Weight                        | 500kg                   |
| Tractor HP                    | 35HP+                   |
| Cutting Height (using wheels) | 25-200mm                |



- Rotors are timed so that they overlap each other and are protected by a flexible drive rubber coupling.and shearbolt backup. Fitted with Italian Series 5 pto shaft with integrated slip clutch.
- Optional 14" Holden wheelkit controls the topping height instead of the skids. Adjusted either via ratchet or hydraulic ram.
- Front and rear rubber flaps are standard with rear one able to be postioned up out of the way so as to not restrict grass flow.
- Pasture toppers are designed specifically for topping and should not be used as a slasher





## John Berends Implements Pty Ltd

email: sales@johnberends.com.au www.johnberendsimplements.com.au